

Floor Graphics Laminate (FR)

IP 2830-201

ImagePerfect™ 2830-201 is a vinyl laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting indoor printed floor graphics.

IP 2830-201

ImagePerfect™ 2830-201 is a textured laminate that provides a non-slip, scuff-resistant surface finish and a high level of transparency. It should be used as a match-component laminate in conjunction with IP 2521 as the print media for indoor floor graphics. The product has excellent anti-slip properties and resistance to wearing. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle.

Specifications	Indoor floor minder vinyl laminate
DESCRIPTION	Clear matt
COLOUR	200µ
THICKNESS	200µ
WEIGHT	N/A
ADHESIVE	Solvent based acrylic, permanent
ADHESIVE STRENGTH	11N / 25mm (Finat TM 1/24h)
RELEASE PAPER	N/A
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	6 months
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on real European exposure conditions. Actual performance will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the removal of carriers can otherwise change the specific features of the product. To ensure the best possible outcome, the media component ImagePerfect™ prints should be used with the correct ImagePerfect™ media.

© Spandex 2015. All rights reserved. www.spandex.com



IP 2521

Indoor Floor Graphics (FR)

ImagePerfect™ 2521 is a white gloss calendered vinyl that has been engineered for the creation of indoor floor graphics. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks (with the exception of 3rd generation inks when used with 300 series printers).

IP 2521

ImagePerfect™ 2521 has been specifically engineered for use as a printable, indoor floor graphic product, with its grey adhesive contributing towards high levels of opacity on the printed output. It can be used for promotional advertising in retail spaces, for point-of-sale and point-of-purchase promotions and for temporary wayfinding graphics and public information displays in locations such as trade shows, exhibitions, airports, museums, art galleries, sports arenas, hotels, etc. The adhesive system should allow for quick and clean removability that leaves no adhesive residue on the substrate. The product must be used in conjunction with its match-component laminate system (IP 2830-201), which offers a textured, scuff-resistant, non-slip surface. Laminate: IP 2830-201.

Attention: Please make sure the printed IP 2521 is completely dry before laminating. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle. Surface preparation: In order to achieve process-secure application, it is essential that the substrate is totally dry and completely free of dust, dirt and debris before the product is installed. As such, we would recommend that the substrate is brushed and vacuumed before the IP 2521 is applied and, if the substrate is wet, we would recommend that it should be dried via portable heating. Please note: When the product is converted on an HP 500 series printer, it is essential that the "cleaning cylinder" is used.

Specifications

DESCRIPTION	Indoor floor graphics
COLOUR	White gloss
THICKNESS	100µ
WEIGHT	N/A
ADHESIVE	Solvent based acrylic, removable, grey
ADHESIVE STRENGTH	16N / 25mm (Finat TM 1/24h)
RELEASE PAPER	Paper, 145g/m ²
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	6 months
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© November 2017 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on real European exposure conditions. Actual performance will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the removal of carriers can otherwise change the specific features of the product. To ensure the best possible outcome, the media component ImagePerfect™ prints should be used with the correct ImagePerfect™ media.

© Spandex 2017. All rights reserved. www.spandex.com

